EUROQUARTZ

GW62 VCXO

CMOS SMD 11.4 x 9.6 x 2.5mm, 6 pad 50.1MHz ~ 800.0MHz

- **Frequency range 50.01MHz to 800MHz**
- **LVCMOS Output**
- **Supply Voltage 3.3 VDC**
- **High Q fundamental mode crystal**
- **Low jitter multiplier circuit**

RoHS



DESCRIPTION

GW62 VCXOs, are packaged in an industry-standard, 6 pad, 11.4 x 9.6 x 2.5mm SMD package. GW62 VCXOs incorporate a high Q fundamental crystal and a low jitter multiplier circuit.

SPECIFICATION

Frequency Range:	50.01MHz to 800.0MHz
Supply Voltage:	3.3 VDC ±5%
Output Logic:	LVCMOS
Integrated Phase Jitter:	2.6ps typical, 4.0ps maximum (for 155.250MHz)
Period Jitter RMS:	4.3ps typical (for 155.250MHz)
Period Jitter Peak to peak:	27.0ps typical (for 155.250MHz)
Phase Noise:	*See table below*
Initial Frequency Accuracy:	Tune to the nominal frequency with Vc= 1.65 ±0.2VDC
Output Voltage HIGH (1):	90% Vdd minimum
Output Voltage LOW (0):	10% Vdd maximum
Pulling Range:	From ±30ppm to ±150ppm
Temperature Stability:	*See table*
Output Load:	15pF
Start-up Time:	10ms maximum, 5ms typical
Duty Cycle:	50% ±5% measured at 50% Vdd
Rise/Fall Times:	1.2ns typical (15pF load)
Current Consumption	
<96MHz:	30mA maximum (15pF load)
>96MHz:	40mA maximum (15pF load)
Linearity:	10% maximum, 6% typical
Modulation Bandwidth:	25kHz minimum
Input Impedance:	2 MΩ minimum
Slope Polarity: (Transfer function)	Monotonic and Positive. (*An increase of control voltage always increases output frequency.*)
Storage Temperature:	-50° to +100°C
Ageing:	±5ppm per year maximum
Enable/Disable (Tristate):	Pads 2 or 5, Enable high or 70% Vdd min applied to Tri-state pad to enable output. 30% Vdd max. to disable output (high impedance)
RoHS Status:	Fully compliant

OUTLINE & DIMENSIONS



Pad Connections

1 Voltage Control (rounded pad)
2 Tri-state*
3 Ground
4 Output
5 Tristate*
6 Supply Voltage

*Pads 2 and 5 are connected internally

PHASE NOISE

Offset	Frequency 155.25MHz
10Hz	-65dBc/Hz
100Hz	-95dBc/Hz
1kHz	-120dBc/Hz
10kHz	-125dBc/Hz
100kHz	-121dBc/Hz
1MHz	-120dBc/Hz
10MHz	-140dBc/Hz

FREQUENCY STABILITY

Stability Code	Stability ±ppm	Temp. Range
A	25	0°~+70°C
B	50	0°~+70°C
C	100	0°~+70°C
D	25	-40°~+85°C
E	50	-40°~+85°C
F	100	-40°~+85°C

If non-standard frequency stability is required
Use 'I' followed by stability, i.e. I20 for ±20ppm

PART NUMBER SCHEDULE

Example: 3GW62B-80N-155.25

- Supply Voltage: 3 = +3.3V
- Series Designator: GW62
- Stability over temperature range (*See table*)
- Pullability in ±ppm
- Pullability determinator: N = minimum, M = maximum, T = Typical
- Frequency in MHz

EUROQUARTZ LIMITED Blacknell Lane CREWKERNE Somerset UK TA18 7HE
Tel: +44 (0)1460 230000 Fax: +44 (0)1460 230001 info@euroquartz.co.uk www.euroquartz.co.uk