

11.4 x 9.6 x 2.5mm SMD

10.0MHz ~ 156.0MHz

FEATURES

- Sine Wave output VCXO
- Output 0dBm into 50Ω load, higher output available
- Harmonics < 20dBc
- Low current consumption

DESCRIPTION

GS42 sine wave VCXOs provide a true sine wave out output. The VCXOs are packaged in the industry-standard, 11.4×9.6 mm SMD package. The VCXO is produced to close tolerances and has low current consumption.

SPECIFICATION

Frequency Range:	10.0MHz to 156.0MHz
Input Voltage:	+3.3±5% or +5.0VDC ±5%
Frequency Stability:	See table
Control Voltage Centre:	+1.65 VDC
Initial Frequency Accuracy:	±15ppm with Conrol V at +1.65VDC
Control Voltage Range:	+0.3V to +3.0VDC
Frequency Deviation Range:	±80ppm typical*
Output Wave Form:	True Sine Wave
Output Level:	0dBM into 50Ω load**
Harmonics:	<-20dBc
Phase Noise:	-140dBc/Hz at 10kHz offset
Current Consumption:	See table
Start-up Time:	6.0ms typical
Storage Temperature:	-50° to +100°C
Sub-Harmonics:	None
Ageing:	±5ppm per year maximum
Enable/Disable:	Not implemented - 4 pad package
RoHS Status:	Fully compliant or non-compliant

- * Wider pulling range available
- ** Higher output <5dBm available

FREQUENCY STABILITY

Stability Code	Stability ±ppm	Temp. Range
Α	25	0°∼+70°C
В	50	0°∼+70°C
С	100	0°~+70°C
D	25	-40°∼+85°C
Е	50	-40°∼+85°C
F	100	-40°∼+85°C
If non-standard frequency stability is required		

If non-standard frequency stability is required Use 'I' followed by stability, i.e. 120 for ±20ppm

CURRENT CONSUMPTION

Frequency	Supply Voltage (±5%)		
rrequerity	+3.3V	+5.0V	
10MHz	9mA	18mA	
100MHz	18mA	34mA	
150MHz	19mA	36mA	





OUTLINE & DIMENSIONS





