


Rugged construction SMD TCXO

10.0MHz to 50.0MHz

- Very rugged construction TCXO
- Industry-standard 7x5mm miniature SMD format
- Tight tolerances over temperature from 0.3ppm
- Wide frequency range, 10MHz to 50MHz
- Available with HCMOS or CLIPPED SINEWAVE outputs



T75 - OUTLINES AND DIMENSIONS



DESCRIPTION

T75 series TCXOs are packaged in the industry-standard 7x5mm miniature SMD format. The parts have a rugged construction, able to withstand up to 100,000g and offer a wide frequency range with close tolerances over temperature. Designed and manufactured by Greenray Industries Inc.

GENERAL SPECIFICATION

Frequency Range:	10.0MHz to 50.0MHz
Output:	HCMOS or Clipped Sinewave
Symmetry:	50%±10% (HCMOS)
Output level	
	Clipped Sine: +0.8Vp-p typical into 10pF/100kOhm
	HCMOS T75: +0.2V max. to +2.8V min
	HCMOS T76: +0.2V max to +4.2V min
Temperature Stability:	See table
Ageing:	<1 ppm/yr at 10MHz (typical)
Frequency adjust:	±4ppm typical via 0 to Vcc control voltage, positive slope.
Supply Voltage:	+3.3VDC ±5% or +5.0VDC
Supply Current	
	HCMOS: <6mA
	Clipped Sine: <2mA

ENVIRONMENTAL

Vibration: per MIL-STD-202G, Meth. 214, Cond. I-F
Shock: per MIL-STD-202G, Meth. 213, Cond. F
(Shock levels to 100,000g are available)

FREQUENCY STABILITY OVER TEMPERATURE

Temperature Stability (°C)	Tolerance	Option
-10 ~ +60	±0.3ppm	G37
-20 ~ +70	±0.5ppm	N57
-40 ~ +85	±0.5ppm	T57
-40 ~ +85	±1.0ppm	T16
-55 ~ +95	±2.0ppm	V26

(Other temperature stabilities are available)

SPECIFYING INFORMATION

Model No:	Input Voltage	Output Type
T75	+3.3V	HCMOS
T76	+5.0V	HCMOS
T77	+3.3V	CLIP SINE
T78	+5.0V	CLIP SINE

T75 - PART NUMBERING PROCEDURE

Example: **T75-G37-20.0MHz**
(Model number - option - frequency)

T75 - CUSTOMISED PARAMETERS

There are a wide variety of custom options available for the T75 series TCXOs. Contact Euroquartz technical sales with your requirements:

info@euroquartz.co.uk